

Cabinet Power Density	Low < 5 kW	Medium 5kW-10kW	Med/High 11kW-20kW	High 21kW-30kW	Very High 31kW-40kW	Extreme >40kW
Hot and cold aisle cabinet layout having cabinet blank-off panels and floor opening with brushes.	X	X	X	X	X	
Suspended ceiling is optional for the air distribution system.	X	X				X
Suspended ceiling is required for the air distribution system.			X	X	X	
CRAH units having a constant volume supply air fan and a two-way modulating control valve.	X	X				
CRAH units having a variable volume supply air fan and a two-way modulating control valve.		X	X	X	X	
Perimeter CRAH units having an underfloor supply air distribution system with a non-ducted return air plenum.	X					
Perimeter CRAH units having an underfloor supply air distribution system with a ducted return air plenum.		X	X	X	X	
Hot or cold aisle containment using plastic strip curtains.		X	X			
Hot or cold aisle containment using panel construction with man doors.			X	X	X	
Hot aisle containment with passive chimneys.			X			
Hot aisle containment with fan assisted chimneys.				X		
Cabinet mounted fans assembly.		X				
Supplemental direct expansion air conditioning units.			X	X		
In-row CRAH units having hot aisle cabinet containment.			X	X		
Cabinet-mounted cooling coils without fans.			X	X		
Cabinet-mounted cooling coils with fans.				X	X	
Water cooled cabinets.					X	X